



## Acoustic Infill

ROCKWOOL® Acoustic Infills consist of a trapezoidal shaped ROCKWOOL insulation which can be engineered to suit all types of perforated metal roof deck profiles.

Acoustic Infills provide a combination of optimised density, fibre direction and excellent fit to deliver significant levels of sound absorption, designed and tested for use within ROCKWOOL HARDROCK® roof systems.

*Acoustic Infills for different deck types, such as those from Joricide, Euro Clad, and Firth Steels, can be made to order subject to minimum order quantities. For further details please contact your local ROCKWOOL sales representative.*

Tissue Faced White

Pallet Size 1200 x 1000mm

Product Code	Deck Type	Length (mm)	Major (mm)	Minor (mm)	Thickness (mm)	Pieces/Pallet	MOQ (Pallet)	List Price/Linear m
303802	TATA D32	1200	68	23	25	952	1	€6.25
303922	TATA D46	1200	116	63	40	340	1	€8.46
303994	TATA D60	1200	106	60	50	275	1	€8.99
303997	TATA D100	1200	120	59	95	140	1	€11.28
303999	TATA D137	1200	161	39	125	90	1	€14.65
304799	TATA D153	1200	157	36	150	81	1	€14.71
304800	TATA D158	1200	128	37	150	99	1	€14.71
304802	TATA D159	1200	138	34	150	99	1	€14.24
304804	TATA D200	1200	166	71	195	56	1	€19.15



Acoustic infill orders cannot be used to contribute towards mixed loads.  
Lead times for these products can vary and will be confirmed on receipt of order.  
Additional carriage charges may be applied.