

Knauf Joint Cement Premium

Data Sheet



Knauf Joint Cement Premium is a lightweight air drying compound for bedding tapes and finishing joints by hand or machine application. Knauf Joint Cement Premium produces an exceptional finish with minimal sanding effort.

Knauf Application

Interior applications only

- For jointing of gypsum boards
- For bedding joint tapes and finishing joints by hand or machine application

Physical Characteristics

Bag Size	Bags per pallet	Material No.	Approx. Coverage
kg			m² per bag
20	42	622337	80 (for two coats of finish)

Storage and Handling

Store dry. Protect against frost, high temperatures and exposure to direct sunlight. Recommended for use within 12 months of manufacture.

Compliance

Bedding filler for interior use acc. to BS EN 13963: 2014

Performance Data

In compliance with BS EN 13963: 2014, the product is subject to initial type testing and continuous factory product control and bears the CE marking.

Technical Data

- Reaction to fire: A2
- Flexural Strength: NPD

Product Features

- 12 months shelf life
- Air drying
- Up to 24 hours drying time (depending on conditions)

Application/Installation

Mixing:

Sprinkle the powder into a suitable clean mixing container with clean, cold tap water.

Allow to stand for 30 minutes.

Bedding and Finishing joint tape:

Apply Knauf Joint Cement Premium to the recess formed by the plasterboard tapers. Apply Knauf Joint Tape, submerging the tape into the compound with a taping knife or trowel.

When dry apply second coat.

If sanding is required, at least 120 grit sandpaper is recommended.

Suitability:

Suitable for use on all plasterboards manufactured to BS EN 520:2004.

Use in accordance with British Standard Code of Practice BS 8212:1995 and BS 8000: Part 8:1994 workmanship.

Cleaning:

Clean containers and tools with water immediately after use.

Build for the world we live in

Related products

Knauf Joint Cement Premium should be used in conjunction with the following products:

Knauf Fill and Finish 30 Premium Material no: 5kg: 622326 Material no: 10kg: 622329



Knauf Fill & Finish 60 Premium Material no: 5kg: 622331 Material no: 10kg: 622332

Knauf Joint Filler Premium Material no: 10kg 622340 Material no: 20kg 622342

Knauf Joint Tape Material no: 258337

Knauf Fibre Tape Material no: 493679



Health & Safety

May irritate eyes or sensitive skin.

Dust may irritate respiratory system.

- Protective gloves, glasses and face mask is recommended.
- Avoid prolonged contact with skin, wash off immediately with water.
- Avoid inhaling minimise dust, ventilate area, move person to fresh air.
- Avoid ingestion wash mouth out immediately and drink plenty of water.
- Should any symptoms persist or allergic reaction occur, seek medical advice

Refer to the product MSDS and also the Knauf Guidance for Safe Material Management document:

MSDS: www.knauf.co.uk/product-data-sheets

Safe Material Management: www.knauf.co.uk/literature

Sustainability Credentials

Please view Product Sustainability Credentials Sheet:

www.knauf.co.uk/product-data-sheets

Customer Service

UK Tel: 0800 521 050 Eire Tel.: 01 4620739 Email: cservice@knauf.co.uk

Technical Service

UK Tel.: 0800 030 4135 Eire Tel.: 01 4620739 E-mail: technical@knauf.co.uk

Literature UK Tel: 03700 613 700 Eire Tel.: +44 3700 613 700

Website

www.knauf.co.uk www.knauf.ie

Knauf Kemsley Fields Business Park Sittingbourne Kent ME9 8SR

Knauf 87 Broomhill Road Tallaght Dublin 24



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2018