

The Xtratherm Warm-R & Warm-R Premium Insulation Boards consists of rigid polystyrene boards cut from moulded blocks of white EPS (Warm-R) or with grey graphite enhancement (Warm-R Premium). The boards are manufactured in square edge, T&G and shiplap jointing. Xtratherm Warm-R & Warm-R Premium Insulation Boards are installed during construction.

Dimensions: 1200mm x 600mm

Profile: Straight edge

Product and Units

Essential Characteristics	Performance	Test Standard
Thermal Conductivity	$\lambda_{_D} = 0.038$ W/m.K	EN 12667
Density	15 kg/m³ ± 2	
Reaction to Fire	NPD	EN 13501-1
Thickness	T2	EN 823
Length	L2	EN 822
Width	W2	EN 822
Squareness	S2	EN 824
Flatness	P3	EN 824
Compressive Strength	CS (10/Y) 70	EN 826
Minimum cross-breaking strength	140 kPa	
Dimensional stability	DS (70,90)1	EN 1604

ISO 9001 ISO 14001 Quality Management Systems Environmental Management

Xtratherm More than insulation

Xtratherm UK Limited Park Road Holmewood Chesterfield, Derbyshire United Kingdom S42 5UY

Sales: +44 (0) 371 222 1033 Tech: +44 (0) 371 222 1055 info@xtratherm.com

xtratherm.com

Xtratherm Limited Liscarton Industrial Estate Kells Rd, Navan Co. Meath, Ireland C15NP79

Sales: +353 (46) 906 6000 Tech: +353 (46) 906 6050 info@xtratherm.ie

xtratherm.ie

UKIDEPSSDA4

