

FI-D Universal / Window Tape Split Release



Roll Sizes:
75mm X 25m
100mm x 25m
150mm x 25m
200mm x 25m



Properties:



Sd value of 40 m.

- Adhesive tape for indoor use.
- Full-surface adhesive coating.

Product description:

Fully adhesive tape for interior use. Due to the stretchability of the film, movements of the building structure are absorbed.

Due to the full-surface adhesive coating, no additional adhesive is required.

Adhesive tape can be plastered over.

Application:

- Application surface may require priming with VENTOS Spray Primer.
- Measure and cut the tape to the length with at least 30mm to spare.
- Peel the cover foil from the self adhesive strip and press the strip to the back of the window frame.
- Continue this all the way around to seal all sides of the window frame.
- The tape is carefully pressed onto the reveal substrate. Ensure that the tapes overlap in the corners.
- Use a pressure roller to ensure optimum pressure adhesion.



FI-D Universal / Window Tape Split Release

Product Data Sheet		
Total weight	EN 1849-2	420 g/m ²
Weight adhesive	EN 1849-2	240 g/m ²
Thickness	EN 1849-2	0,49 mm
Tear strength MD/CD*	EN 12311-1	300 / 55 N/50mm
Elongation MD/CD*	EN 12311-1	25 / 135%
Max. permissible total deformation		5%
Air tightness	EN 1026	a _n ≤0,1
Water tight. against driving rain	EN 1027	-
Resistance to water passage	EN 13984/EN 1928	W1 (Water column >2000 mm)
Sd value	EN 1931/EN 12572	40 m
Fire behaviour	EN ISO 11925-2	E
UV resistance		3 months
Temperature resistance		-40° /+80°C
Application temperature		-5°+40°C
Storage location		dry and frost-free in original container
Storage time		max. 12 months

*MD = longitudinal CD = transverse

