



# TIMBER FRAME ROLL 35



## Thermal Insulation for Timber Frame Walls

Timber Frame Roll 35 is a glass mineral wool roll providing thermal performance and acoustic benefits in timber frame walls. The strong, resilient and flexible rolls are pre-cut to 2 x 570mm (to fit between standard 600mm stud centres) or 3 x 400mm widths.

## Features and Benefits

**Thermal**

**Thermal performance**  
Thermal conductivity of 0.035 W/m.K. Helps to reduce heat loss within the building envelope and decrease energy costs.

**Non-combustible**

**Non-combustible**  
Achieves a Euroclass A1 Reaction to Fire classification, according to BS EN 13501-1.

**Acoustic**

**Acoustic benefits**  
Reduces unwanted noise from external sources helping to improve the acoustic comfort of those living within the building.

**Easy to install**

**Quick and easy to install**  
Push fits between timber stud centres with no need for additional fixings.

**Recycled glass**

**Recycled glass**  
Manufactured from up to 75% recycled glass.

## Product Specification

Product code	Thickness (mm)	Width (mm)	Length (mm)	Pack area (m <sup>2</sup> )	Packs per pallet	Pallet area (m <sup>2</sup> )	λ <sub>0</sub> Declared thermal conductivity (W/m.K)	R <sub>0</sub> Declared thermal resistance (m <sup>2</sup> .K/W)
5200625583	140	2 x 570	4000	4.56	18	82.08	0.035	4.00
5200822660	140	3 x 400	4000	4.80	18	86.40	0.035	4.00



# CHARACTERISTICS

Characteristic	Description
<b>Thermal</b>	Timber Frame Roll 35 has a declared thermal conductivity of 0.035 W/m.K under BS EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.
<b>Fire</b>	Euroclass A1 Reaction to Fire classification according to BS EN 13501-1.
<b>Environmental</b>	All ISOVER products are manufactured under Environmental Management System - ISO 14001. Zero Ozone Depletion Potential (ODP) and Global Warming Potential (GWP) < 5. The manufacturing process does not use or contain CFC's, HCFC's or other damaging gases. BES 6001 Rating "Good" - The Framework Standard for Responsible Sourcing.
<b>BRE statements</b>	Timber Frame Roll 35 corresponds to the BRE Global Green Guide online generic specification glass wool insulation ref 815320003, which achieves a summary rating of A+ within the Domestic, Health, Industrial, Commercial, Retail and Education categories.
<b>Quality</b>	All ISOVER products are manufactured under Quality Management Standard - ISO 9001. Timber Frame Roll 35 is manufactured in accordance with BS EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.
<b>Building regulations</b>	Helps to meet the requirements of thermal building regulations.
<b>Recycled content</b>	Timber Frame Roll 35 is manufactured from up to 75% recycled glass.
<b>Durability</b>	Thermal conductivity of mineral wool products does not change with time. Experience has shown the fibre structure to be stable and the fibre matrix contains no other gases than atmospheric air (see standard EN 13162). Will not sustain vermin, nor breed or promote fungi or bacteria.
<b>Handling and storage</b>	Information regarding storage, installation and handling of ISOVER products, or health & safety information, can be found here.
<b>Health and safety</b>	
<b>Certification</b>	CE marked (1121-CPR-BA0053) to BS EN 13162. Designation code: MW-EN 13162-T1.

## Customer Service Centre - Order Placement and Enquiries

**Tel:** +353 (1) 629 8444

**Fax:** +353 (1) 623 7055

**Email:** [customer.service@saint-gobain.com](mailto:customer.service@saint-gobain.com)

## ISOVER Address:

Unit 4, Kilcarbery Business Park,  
Nangor Rd, Dublin 22, D22 R2Y7, Ireland

## Technical Enquiries - Advice and Support Line

**ROI:** 1800 744 480

**NI:** 0845 399 0159

**Email:** [tech.ie@saint-gobain.com](mailto:tech.ie@saint-gobain.com)

**isover.ie**