
Product Information Sheet







Product Name VARIO XtraSafe

This intelligent membrane (Water Vapour retarder) offers a higher variability for optimum protection, and works best when combined with Vario XtraFix Adhesive Fixture tape.

Part of the Vario range



















BENEFITS AND FEATURES

IV	ı M	ΙЕ	וח	Αl

Modified polyamide with polyolefin layer, strengthened with special nonwoven fabric

FIRE

Euroclass E (normally flammable) in accordance with DIN 13984.

MOISTURE

Vapour permeable breathable insulation. Improves energy performance and reduces heating & cooling costs.

EASY TO INSTALL

The membrane can be simply and quickly installed by just one worker.

TEMPERATURE

 $(-40^{\circ}\text{C to} + 80^{\circ}\text{C.})$

WATER VAPOUR DIFFUSION

Approx. 70 g/m^2d to 1.2 g/m^2d in accordance with EN 12572.

STANDARDS & CERTIFICATION

QUALITY

We hold a Quality Management Standard BS EN ISO 9001: 2008 for manufacturing.

CE

All products are manufactured in accordance with the CE marking requirements under the Construction Products Regulation,

PRODUCT STANDARDS

All our products are manufactured in accordance with product standard: BS EN 13162: 2008 and BS EN 13172 Evaluation of Conformity.

ENVIRONMENT

ISOVER is an ISO 14001:2004 (Environmental Management System) accredited manufacturing facility. This accreditation ensures that all products are manufactured to the stringent standards set out by this management system. EN ISO 13162 EMS 551706 003 BS EN ISO 9001: 2000



VARIO XtraSafe Application



Timber Frame

Insulation between studs

- 1 External brick
- 2 Cavity
- 3 Breather membrane
- 4 Sheathing board
- 5 ISOVER insulation between studs
- 6 XtraSafe membrane
- 7 12.5mm Gyproc WallBoard
- 8 XtraFix Adhesive fixative tape

For more applications and product details, please visit www.isover.ie



Basic Installation Steps





Stick Vario XtraFix on a firm surface
 i.e. Timber Rafters. If necessary, affix
 additionally at 20 cm gaps

2. Affix the Vario XtraSafe Intelligent membrane against the Vario XtraFix. Lay subsequent strips with a 10 cm overlap.

ISOVER Ireland Unit 4, Kilcarbery Business Park, Nangor Rd., Dublin 22 Tel: +353 (0) 1 629 8400 Email: info@isover.ie Web: www.isover.ie ISOVER Technical Team ROI Free Phone: 1800 744 480 NI Phone: 0845 399 0159 Email: tech.ie@saint-gobain.com

