

EARTHWOOL FACTORYCLAD ROLL

March 2018



APPLICATIONS



DESCRIPTION

For thermal and acoustic insulation of roofs and external walls in profiled metal clad buildings and portable buildings. Earthwool FactoryClad is available in a range of thicknesses and thermal conductivities to provide the designer with ultimate flexibility.

It is 1200mm wide to suit commonly used rail and bracket spacings and has an unbeatable A1 Reaction to Fire rating.

PERFORMANCE

Thermal

Thermal conductivity: 0.040 W/mK and 0.032W/mK

Fire

Classification: EUROCLASS A1 to BS EN 13501-1

Vapour resistivity

Water vapour resistivity: 5.00MNs/g.m

BENEFITS

- ✓ Euroclass A1 non-combustible
- ✓ Superior thermal performance
- ✓ Exceptionally high tear resistance
- ✓ Provides thermal and acoustic performance
- ✓ Lightweight for ease of installation

SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m ² K/W)	Length (m)	Width (mm)	Area per pack (m ²)
Earthwool FactoryClad Roll 40					
220	0.040	5.50	4.35	1200	5.22
200	0.040	5.00	4.85	1200	5.82
180	0.040	4.50	6.26	1200	7.51
160	0.040	4.00	7.05	1200	8.46
140	0.040	3.50	8.02	1200	9.62
120	0.040	3.00	9.40	1200	11.28
100	0.040	2.50	11.25	1200	13.50
80	0.040	2.00	14.10	1200	16.92
Earthwool FactoryClad Roll 32					
80	0.032	2.50	5.00	1200	6.00

All dimensions are nominal

CERTIFICATION



challenge.
create.
care.

EARTHWOOL FACTORYCLAD ROLL

March 2018

ADDITIONAL INFORMATION

Durability

Earthwool FactoryClad Rolls are odourless, rot proof, non-hygroscopic, do not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

Application

Earthwool FactoryClad Rolls are used for the thermal and acoustic insulation of roofs and walls in profiled metal clad buildings and portable buildings. With a Euroclass A1 fire classification, their use can potentially reduce insurance premiums compared to foam composite panels. Earthwool FactoryClad Rolls are manufactured 1200mm wide to suit commonly used rail and bracket systems and in long lengths, making them particularly suitable for use in twin skin profiled metal cladding systems and standing seam roofs.

Standards

Earthwool FactoryClad Rolls are manufactured in accordance with BS EN 13162, ISO 50001 Energy Management Systems, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by Bureau Veritas.

Environmental

Earthwool FactoryClad Rolls represent no known threat to the environment and have zero Ozone Depletion Potential and zero Global Warming Potential.

Vapour resistivity

Earthwool FactoryClad Rolls offer negligible resistance to the passage of water vapour and have a water vapour resistivity of 5.00 MNs/g.m.

Handling and storage

Earthwool FactoryClad Rolls are easy to handle and install, being lightweight and easily cut to size, where necessary. They are supplied in polythene packs which are designed for short term protection only. For longer term protection on site, the products should be stored either indoors, or under cover and off the ground. Earthwool FactoryClad Rolls should not be left permanently exposed to the elements.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

Knauf Insulation Ltd

PO Box 10, Stafford Road, St.Helens,
Merseyside, WA10 3NS. UK

Customer Service: 0844 800 0135

Technical Support Team: 01744 766 666

Literature: 08700 668 660

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE1505DAT

challenge.
create.
care.