

EARTHWOOL FRAMETHERM SLAB

March 2018



APPLICATIONS



DESCRIPTION

Earthwool FrameTherm is a specialist product for timber frame construction. FrameTherm slabs are manufactured with a width of 570mm to suit studs spaced at 600mm centres. They are available in a range of thermal conductivities to provide design flexibility and have an unbeatable A1 Reaction to Fire rating.

PERFORMANCE

Thermal

Thermal conductivity: From 0.032 to 0.038W/mK

Fire

Classification: EUROCLASS A1 to BS EN 13501-1

Vapour resistivity

Water vapour resistivity: 5.00MN/g.m

BENEFITS

- ✓ Euroclass A1 non-combustible
- ✓ For friction fitting between timber studs at 600mm centres
- ✓ Easy to handle and install
- ✓ Excellent sound absorption

SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m ² K/W)	Length (mm)	Width (mm)	Slabs per pack	Area per pack (m ²)
Earthwool FrameTherm Slab 38						
140	0.038	3.65	1170	570	8	5.34
90	0.038	2.35	1170	570	12	8.00
Earthwool FrameTherm Slab 35						
140	0.035	4.00	1170	570	6	4.00
90	0.035	2.55	1170	570	8	5.34
Earthwool FrameTherm Slab 32						
140	0.032	4.35	1170	570	4	2.67

All dimensions are nominal

CERTIFICATION



challenge.
create.
care.

EARTHWOOL FRAMETHERM SLAB

March 2018

ADDITIONAL INFORMATION

Durability

Earthwool FrameTherm Slabs are odourless, rot proof, non-hygroscopic, do not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

Application

Earthwool FrameTherm Slabs are used for the thermal insulation of external walls and warm roofs in timber frame construction and are friction fitted between studs and rafters.

Standards

Earthwool FrameTherm Slabs are manufactured in accordance with BS EN 13162, ISO 50001 Energy Management Systems, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by Bureau Veritas.

Environmental

Earthwool FrameTherm Slabs represent no known threat to the environment and have zero Ozone Depletion Potential and zero Global Warming Potential.

Vapour resistivity

Earthwool FrameTherm Slabs offer negligible resistance to the passage of water vapour and have a water vapour resistivity of 5.00 MNs/g.m.

Handling and storage

Earthwool FrameTherm Slabs are easy to handle and install, being lightweight and easily cut to size, where necessary. Both are supplied in polythene packs which are designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Earthwool FrameTherm Rolls and Slabs should not be left permanently exposed to the elements.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

Knauf Insulation Ltd

PO Box 10, Stafford Road, St.Helens,
Merseyside, WA10 3NS. UK

Customer Service: 0844 800 0135

Technical Support Team: 01744 766 666

Literature: 08700 668 660

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE1506DAT

challenge.
create.
care.